

## Diversions Velvet

GUESTROOM CARPET

**Max System Series** – Milliken’s Max System Products are streamlined to meet performance requirements while providing the absolute best value and service in the industry. Low minimums and emergency response are not a problem when you combine the Max Color System with Milliken’s Service Series Bases. All Max System bases are available for 14 to 21 day shipment, the fastest and most flexible quick ship program in the industry.

### Specifications:

|  |  |
|--|--|
| Fabric Construction                            | Tufted, Patterned Cut Pile   |
| Carpet Fiber                                   | WearOn® Continuous Filament Nylon                                    |
| Stain & Soil Protectant                        | MilliGuard®  |
| Mold/Mildew Odor Control                       | AlphaSan®  |
| Yarn Weight                                    | 24 Oz. Square Yard / <b>814 gm/m<sup>2</sup> (tufted, unshaired)</b> |
| Tufting Gauge                                  | 1/8 Gauge  |
| Stitches Per Inch                              | 8.95 Stitches Per Inch / <b>35.2 Stitches per 10 cm</b>              |
| Tufting Density                                | 71.6 Tufts/Square Inch / <b>1110 10 cm<sup>2</sup></b>               |
| Finished Pile Thickness                        | Nominal .34" Sheared / <b>Nominal 8.6 mm Sheared</b>                 |
| Total Thickness                                | Nominal .42" Sheared / <b>Nominal 10.6 mm Sheared</b>                |
| Density Factor                                 | 198,723  |
| Total Weight                                   | 55 Oz./Square Yard / <b>1865 gm/m<sup>2</sup></b>                    |
| Primary Backing                                | Synthetic Woven  |
| Secondary Backing                              | Synthetic Actionbac®   |
| Width  | 13 feet 6 inches / <b>4.12 m</b>                                     |
| Radiant Panel Test                             | Class I, Greater Than .45 Watts/cm <sup>2</sup>                      |
| Smoke Chamber Test                             | Less Than 450 Flaming & Non-Flaming                                  |
| Static Electricity (AATCC-134) 20% R.H., 70 F) | < 3.5 KV   |
| Recommended Maintenance                        | MilliCare Environmental Services®                                    |
| Recommended Traffic                            | Hotel Guestrooms   |

*Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.*

### Optional Features Available:

|                   |            |
|-------------------|------------|
| Bleach Resistance | ColorSeal® |
|-------------------|------------|

### Applicable Milliken Warranties include:

|                                       |  |
|---------------------------------------|--|
| 10 Year 10% Fiber Loss Wear Warranty  | Edge ravel                                 |
| MilliGuard 5 Year Stain/Soil Warranty | Flammability                               |
| Atmospheric fading                    | Antistatic                                 |
| Delamination of backing               | <b>Additional warranties if purchased:</b> |
| Tuft bind                             | Bleach resistance (ColorSeal®)             |
| Floor compatibility                   |  |
| Antimicrobial protection (AlphaSan®)  |  |

