

# Diversions

GUESTROOM CARPET

**Max System Series** – Milliken’s Max System Products are streamlined to meet performance requirements while providing the absolute best value and service in the industry. Low minimums and emergency response are not a problem when you combine the Max Color System with Milliken’s Service Series Bases. All Max System bases are available for 14 to 21 day shipment, the fastest and most flexible quick ship program in the industry.

**Specifications:**

Fabric Construction	Tufted, Patterned Cut Pile
Carpet Fiber	WearOn® Continuous Filament Nylon
Stain and Soil Protectant	MilliGuard®
Mold/Mildew Odor Control	AlphaSan®
Yarn Weight	32 Oz. Square Yard / <b>1085 gm/m<sup>2</sup></b>
Tufting Gauge	1/10 Gauge
Stitches Per Inch / Stitches Per 10 cm	10.75 Stitches per Inch / <b>42.3 Stitches per 10 cm</b>
Tufting Density	107.5 Tufts/Square Inch / <b>1666/10 cm<sup>2</sup></b>
Density Factor	403,790
Finished Pile Thickness	Nominal .23" Sheared / Nominal 5.8 mm Sheared
Total Thickness	Nominal .31" Sheared / Nominal 7.9 mm Sheared
Total Weight	64 Oz./Square Yard / <b>2170 gm/m<sup>2</sup></b>
Primary Backing	Synthetic Woven
Secondary Backing	Synthetic Actionbac®
Width	13' 6" / <b>4.12m</b>
Radiant Panel Test	Class I, Greater Than .45 Watts/cm <sup>2</sup>
Smoke Chamber Test	Less Than 450 Flaming & Non-Flaming
Static Electricity (AATCC-134) 20% R.H., 70 F)	< 3.5 KV
Recommended Maintenance	MilliCare Environmental Services®
Recommended Traffic	Hotel Guestrooms

*Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.*

**Optional Features Available:**

Bleach Resistance	ColorSeal®
-------------------	------------

**Applicable Milliken Warranties include:**

10 Year 10% Fiber Loss Wear Warranty	Edge ravel
MilliGuard 5 Year Stain/Soil Warranty	Flammability
Atmospheric fading	Antistatic
Delamination of backing	<b>Additional warranties if purchased:</b>
Tuft bind	Bleach resistance (ColorSeal®)
Floor compatibility	
Antimicrobial protection (AlphaSan®)	

