

Empire

Milliken Performer Series - Milliken's Performer Series Products are constructed for heavy commercial hospitality environments and come standard with 2 of Milliken's proprietary enhancement technologies. 1-StainSmart which provides resistance, repellency and releasability of stains and soil. 2-ColorSeal which provides bleach resistance properties. No other pattern carpet in the Hospitality Industry can offer a performance product that covers all your carpet concerns. Milliken backs the Performer Series with unmatched warranties for wear, stain, soil and bleach.

Specifications:

Fabric Construction	Tufted, Patterned Cut Pile, Dye Injected
Carpet Fiber	Invista® XTI Continuous Filament Nylon, Type 6,6
Stain and Soil Protectant	StainSmart®
Mold/Mildew Odor Control	AlphaSan®
Bleach Resistance	ColorSeal®
Yarn Weight	42 Oz. Square Yard / 1424 gm/m ²
Tufting Gauge	1/10 Gauge
Stitches Per Inch / Stitches Per 10 cm	11.85 Stitches Per Inch / 46.79 Stitches per 10 cm
Tufting Density	118.5 Tufts Per Square Inch / 1837/10 cm ²
Density Factor	445,108
Finished Pile Thickness	Nominal .30" Sheared / Nominal 7.6 mm Sheared
Total Thickness	Nominal .38" Sheared / Nominal 9.7 mm Sheared
Total Weight	73 Oz. Per Square Yard / 2475 gm/m ²
Primary Backing	Synthetic Woven
Secondary Backing	Synthetic Actionbac®
Width	13' 6" / 4.12m
Radiant Panel Test	Class I, Greater Than .45 Watts/cm ²
Smoke Chamber Test	Less Than 450 Flaming & Non-Flaming
Static Electricity (AATCC-134) 20% R.H. , 70 F)	Less Than 3.5 KV

Recommended Maintenance	MilliCare Environmental Services®
Recommended Traffic	Heavy Commercial

Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

Optional Features Available:

Carpet Widths	9 foot, 12 foot - 2,500 sy minimum order requirement
Secondary Backing	PermaBac2 - Moisture Barrier Pad
Secondary Backing	Attached pad - ENHANCER™ TECHNOLOGY
Finished Pile Thickness/Pad	Nominal .30" Sheared / Nominal 7.6 mm Sheared
Total Thickness/Pad	Nominal .51" Sheared / Nominal 12.8 mm Sheared
Total Weight/Pad	108 Oz./Square Yard / 3627 gm/m ²

Applicable Milliken Warranties include:

10 Year 10% Fiber Loss Wear Warranty	Edge ravel
Staining/Soiling (StainSmart®)	Antistatic
Bleach resistance (ColorSeal®)	Tuft bind
Antimicrobial protection (AlphaSan®)	Atmospheric fading
Floor compatibility	Additional warranties if purchased:
Flammability	Attached cushion resiliency
Delamination of backing	Attached cushion moisture barrier

