

# GRAND PLAZA® 36

MODULAR - 100% NYLON

**Modular Series-** Milliken's Modular Series bases are standard with a moisture barrier attached pad and are constructed for the most demanding hospitality environments. Our proprietary modular patterning technology allows for exact pattern match resulting in total design flexibility. You will get uncompromising beauty and relentless durability with Milliken's Modular Series. No other product comes with stronger performance warranties.

**Specifications:**

Fabric Construction	Tufted, Patterned, Cut Pile Carpet Tile
Carpet Fiber	Invista® XTI Continuous Filament Nylon, Type 6,6
Stain and Soil Protectant	StainSmart®
Mold/Mildew Odor Control	AlphaSan®
Dye Method	Milliken High-Definition Ever Technology®
Yarn Weight	36 Oz. Square Yard / <b>1220 gm/m<sup>2</sup></b> (Nominal: Plus or Minus 5% Sheared)
Tufting Gauge	1/10 Gauge
Stitches Per Inch	11.4 Stitches per Inch / <b>44.9 Stitches per 10 cm</b>
Tufting Density	114 Tufts per Square Inch / <b>1767/10 cm<sup>2</sup></b>
Density Factor	427,078
Finished Pile Thickness	.30" Sheared / <b>7.6 mm Sheared</b> (Nominal: Plus or Minus 5%)
Total Thickness	.485" Sheared / <b>12.3 mm Sheared</b> (Nominal: Plus or Minus 5%)
Total Weight	131 Oz./Square Yard / <b>4441 gm/m<sup>2</sup></b> (Nominal: Plus or Minus 5%)
Primary Backing	Synthetic Non-woven
Secondary Backing	Attached pad - ENHANCER™ TECHNOLOGY
Tile Size	36" x 36" / <b>91.44cm x 91.44cm</b>
Radiant Panel Test	Class I, Greater Than .45 Watts/cm <sup>2</sup>
Smoke Chamber Test	Less Than 450 Flaming & Non-Flaming
Static Electricity (AATCC-134) 20% R.H. , 70 F)	< 3.0 KV
Recommended Maintenance	MilliCare Environmental Services®
Recommended Traffic	Heavy Commercial

*Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.*

**Applicable Milliken Warranties include:**

10 Year 10% Fiber Loss Wear Warranty	Floor Compatibility
Staining/Soiling (StainSmart®)	Antistatic
Atmospheric Fading	Tuft Bind
Delamination of Backing	Flammability
Edge Ravel	Cushion Resiliency
Antimicrobial Protection (AlphaSan®)	Floor Release
Heavy Wheeled Traffic	Dimensional Stability
Moisture Resistance	TractionBack® Tile

