

**GRAND PLAZA<sup>®</sup>** MODULAR - WOOL/NYLON BLEND

**Specifications:**

Fabric Construction	Tufted, Patterned, Cut Pile Carpet Tile
Carpet Fiber	Worsterlon <sup>®</sup> 80/20 Wool/Nylon Blend / (Plus or Minus 5% for blend combination)
Stain and Soil Protectant	MilliGuard <sup>®</sup>
Mold/Mildew Odor Control	AlphaSan <sup>®</sup>
Dye Method	Milliken High-Definition Ever Technology <sup>®</sup>
Yarn Weight	40 Oz. Square Yard / 1356 gm/m <sup>2</sup> / (Tufted, Unsheared)
Gauge	1/8 Gauge
Stitches per Inch / Stitches per 10 cm	10.65 Stitches per Inch / 41.9 Stitches Per 10 cm
Tufting Density	85.2 Tufts/Square Inch / 1321 10cm <sup>2</sup>
Density Factor	439,649
Finished Pile Thickness	.28" Sheared / 7.1 mm Sheared / (Nominal: Plus or Minus 5%)
Total Thickness	.475" Sheared / 12.1 mm Sheared / (Nominal: Plus or Minus 5%)
Total Weight	130 Oz./Square Yard / 4407 gm/m <sup>2</sup> / (Nominal: Plus or Minus 5%)
Primary Backing	Synthetic Non-woven
Secondary Backing	Attached pad - ENHANCER <sup>™</sup> TECHNOLOGY
Tile Size	36" x 36" / 91.44 cm x 91.44 cm
Radiant Panel Test	Class I, Greater Than .45 Watts/cm <sup>2</sup> .
Smoke Chamber Test	Less Than 450 Flaming & Non-Flaming
Recommended Maintenance	MilliCare Environmental Services <sup>®</sup>
Recommended Traffic	Heavy Commercial

*Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.*

**Applicable Milliken Warranties include:**

MilliGuard 5 year Stain/soil Warranty	Floor Compatibility
Heavy Wheeled Traffic	Antistatic
Cushion Resiliency	Tuft Bind
Delamination of Backing	Flammability
Edge Ravel	TractionBack <sup>®</sup> Tile
Antimicrobial Protection (AlphaSan <sup>®</sup> )	Floor Release
Atmospheric Fading	Dimensional Stability
Moisture Resistance	

