

# MAX 36

**Max System Series** – Milliken’s Max System Products are streamlined to meet performance requirements while providing the absolute best value and service in the industry. Low minimums and emergency response are not a problem when you combine the Max Color System with Milliken’s Service Series Bases. All Max System bases are available for 14 to 21 day shipment, the fastest and most flexible quick ship program in the industry.

**Specifications:**

Fabric Construction	Tufted, Patterned Cut Pile
Carpet Fiber	WearOn® Continuous Filament Nylon
Stain and Soil Protectant	MilliGuard®
Mold/Mildew Odor Control	AlphaSan®
Yarn Weight	36 Oz. Square Yard / 1220 gm/m <sup>2</sup>
Tufting Gauge	1/10 Gauge
Stitches Per Inch	11.3 Stitches Per Inch / <b>44.5 Stitches per 10 cm</b>
Tufting Density	113 Tufts Per Square Inch / <b>1752/10 cm<sup>2</sup></b>
Finished Pile Thickness	Nominal .25" Sheared / <b>Nominal 6.4 mm Sheared</b>
Total Thickness	Nominal .33" Sheared / <b>Nominal 8.4 mm Sheared</b>
Density Factor	424,449
Total Weight	69.76 Oz. Per Square Yard / <b>2365 gm/m<sup>2</sup></b>
Primary Backing	Synthetic Woven
Secondary Backing	Synthetic Actionbac®
Width	13' 6" / 4.12m
Radiant Panel Test	Class I, Greater Than .45 Watts/cm <sup>2</sup>
Smoke Chamber Test	Less Than 450 Flaming & Non-Flaming
Static Electricity (AATCC-134) 20% R.H. , 70 F)	< 3.5 KV
Recommended Maintenance	MilliCare Environmental Services®
Recommended Traffic	Heavy Commercial

*Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.*

**Optional Features Available:**

Bleach Resistance	ColorSeal®
Secondary Backing	PerformaBac2 - Moisture Barrier Pad
Secondary Backing	Attached pad - ENHANCER™ TECHNOLOGY
Finished Pile Thickness/Pad	Nominal .25" Sheared / <b>Nominal 6.4 mm Sheared</b>
Total Thickness/Pad	Nominal .46" Sheared / <b>Nominal 11.6 mm Sheared</b>
Total Weight/Pad	103.76 Oz./Square Yard / <b>3517 gm/m<sup>2</sup></b>

**Applicable Milliken Warranties include:**

10 Year 10% Fiber Loss Wear Warranty	Edge ravel
MilliGuard 5 Year Stain/Soil Warranty	Flammability
Atmospheric fading	Antistatic
Delamination of backing	<b>Additional warranties if purchased:</b>
Tuft bind	Bleach resistance (ColorSeal®)
Floor compatibility	Attached cushion moisture barrier
Antimicrobial protection (AlphaSan®)	Attached cushion resiliency

