

# Royal

**Milliken Performer Series** - Milliken's Performer Series Products are constructed for heavy commercial hospitality environments and come standard with 2 of Milliken's proprietary enhancement technologies. 1-StainSmart which provides resistance, repellency and releasability of stains and soil. 2-ColorSeal which provides bleach resistance properties. No other pattern carpet in the Hospitality Industry can offer a performance product that covers all your carpet concerns. Milliken backs the Performer Series with unmatched warranties for wear, stain, soil and bleach.

**Specifications:**

Fabric Construction	Tufted, Patterned Cut Pile
Carpet Fiber	Invista® XTI Continuous Filament Nylon, Type 6,6
Stain and Soil Protectant	StainSmart®
Bleach Resistance	ColorSeal®
Mold/Mildew Odor Control	AlphaSan®
Yarn Weight	36 Oz. Square Yard / 1220 gm/m <sup>2</sup>
Tufting Gauge	1/10 Gauge
Stitches Per Inch	11.3 Stitches Per Inch / 44.5 Stitches per 10 cm
Tufting Density	113 Tufts Per Square Inch / 1752/10 cm <sup>2</sup>
Finished Pile Thickness	Nominal .25" Sheared / Nominal 6.4 mm Sheared
Total Thickness	Nominal .33" Sheared / Nominal 8.4 mm Sheared
Density Factor	424,449
Total Weight	69.76 Oz. Per Square Yard / 2365 gm/m <sup>2</sup>
Primary Backing	Synthetic Woven
Secondary Backing	Synthetic Actionbac®
Width	13' 6" / 4.12m
Radiant Panel Test	Class I, Greater Than .45 Watts/cm <sup>2</sup>
Smoke Chamber Test	Less Than 450 Flaming & Non-Flaming
Static Electricity (AATCC-134) 20% R.H. , 70 F)	< 3.5 KV
Recommended Maintenance	MilliCare Environmental Services®
Recommended Traffic	Heavy Commercial

*Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.*

**Optional Features Available:**

Carpet Widths	9 foot, 12' foot - 250 yd minimum order requirement
Secondary Backing	PerformaBac2 - Moisture Barrier Pad
Secondary Backing	Attached pad - ENHANCER™ TECHNOLOGY
Finished Pile Thickness/Pad	Nominal .25" Sheared / Nominal 6.4 mm Sheared
Total Thickness/Pad	Nominal .46" Sheared / Nominal 11.6 mm Sheared
Total Weight/Pad	103.76 Oz./Square Yard / 3517 gm/m <sup>2</sup>

**Applicable Milliken Warranties include:**

10 Year 10% Fiber Loss Wear Warranty	Edge ravel
Staining/Soiling (StainSmart®)	Antistatic
Bleach resistance (ColorSeal®)	Tuft bind
Antimicrobial protection (AlphaSan®)	Atmospheric fading
Floor compatibility	<b>Additional warranties if purchased:</b>
Flammability	Attached cushion resiliency
Delamination of backing	Attached cushion moisture barrier

