

# Grand Plaza® 36

Milliken's Modular Series bases are standard with a moisture barrier attached pad and are constructed for the most demanding hospitality environments. You will enjoy pattern match, uncompromising beauty and relentless durability with Milliken's Modular Series. No other product comes with stronger performance warranties.

<b>Construction</b>	Tufted, Patterned Cut-Pile Carpet Tile
<b>Dye Method</b>	Digital Millitron® Dye Injection
<b>Face Fiber</b>	Milliken WearOn® BCF Nylon Type 6,6
<b>Stain and Soil Protectant</b>	StainSmart®
<b>Mold/Mildew Odor Control</b>	AlphaSan® Built-In Protection
<b>Tufted Face Weight</b>	36 oz./sq.yd. (1,220.7 g./sq.m.)
<b>Tufting Gauge</b>	1/10 (39.4/10 cm.)
<b>Stitches</b>	11.4/in. (44.8/10 cm.)
<b>Tufting Density</b>	114.0/sq.in. (1,765.1/100 sq.cm.)
<b>Finished Pile Height</b>	0.25 in. sheared (6.4 mm.)
<b>Average Density</b>	5,184
<b>Primary Backing</b>	Synthetic Woven/Non-Woven Composite
<b>Secondary Backing</b>	PVC-Free Comfort Plus® ES Cushion
<b>Recycled Content</b>	23% Pre-Consumer
<b>Nominal Total Thickness</b>	0.42 in. sheared (10.7 mm.)
<b>Tile Size</b>	36" x 36" (914.4 x 914.4 mm.)
<b>Nominal Total Weight</b>	120.0 oz./sq.yd. (4,068.9 g./sq.m.)
<b>Flammability (Radiant Panel ASTM-E-648)</b>	≥ 0.45 (Class I)
<b>Smoke Density (NFPA-258-T or ASTM-E-662)</b>	≤ 450 Flaming and Non-Flaming
<b>Static Electricity (AATCC-134) 20% R.H., 70° F.</b>	≤ 3.5 KV
<b>Dimensional Stability – Aachener Test (DIN Std 54318)</b>	≤ 0.2%
<b>Texture Appearance Retention Rating (TARR)</b>	Severe Traffic End-Use Applications
<b>Recommended Maintenance</b>	MilliCare® Textile and Carpet Care Service Network
<b>Indoor Air Quality – CRI Green Label Plus™</b>	GLP0793, Carpet Category 5Y

Design © Milliken & Company. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice.



## Warranties:

Wear - 10 Year / 10% Fiber Loss  
Staining/Soiling (StainSmart)  
Atmospheric Fading  
Delamination of Backing  
Antimicrobial Protection (AlphaSan)  
Edge Ravel

Flammability  
Antistatic  
Tuft Bind  
Dimensional Stability  
Heavy Wheeled Traffic  
Floor Compatibility

Floor Release  
Moisture Resistance  
Cushion Resiliency