

# StratoAlto 32 Modular

The Strato base is made possible through Milliken's Convergence™ Technology, which combines precision, multi-level Infinity™ tufting with digital patterning to create a highly dimensional and textural product. Milliken's Modular Series bases are standard with a moisture barrier attached pad and are constructed for the most demanding hospitality environments. You will enjoy pattern match, uncompromising beauty and relentless durability with Milliken's Modular Series. No other product comes with stronger performance warranties.

<b>Construction</b>	Infinity™ Tufted, Precision Multi-Level Loop Tip Shear
<b>Dye Method</b>	Digital Millitron® Dye Injection
<b>Face Fiber</b>	Milliken WearOn® BCF Nylon Type 6,6
<b>Stain and Soil Protectant</b>	StainSmart®
<b>Mold/Mildew Odor Control</b>	AlphaSan® Built-In Protection
<b>Tufted Face Weight</b>	32 oz./sq.yd. (1,085.0 g./sq.m.)
<b>Tufting Gauge</b>	1/12 (47.2/10 cm.)
<b>Stitches</b>	11.5/in. (45.3/10 cm.)
<b>Tufting Density</b>	138.0/sq.in. (2,138.2/100 sq.cm.)
<b>Finished Pile Height</b>	0.23 in. high/0.09 in. low (5.8/2.3 mm.)
<b>Average Density</b>	5,009
<b>Primary Backing</b>	Synthetic Non-Woven
<b>Secondary Backing</b>	PVC-Free Comfort Plus® ES Cushion
<b>Recycled Content</b>	24% Pre-Consumer, 1% Post-Consumer
<b>Nominal Total Thickness</b>	0.47 in. sheared (11.9 mm.)
<b>Tile Size</b>	36" x 36" (914.4 x 914.4 mm.)
<b>Nominal Total Weight</b>	127.2 oz./sq.yd. (4,313.0 g./sq.m.)
<b>Flammability (Radiant Panel ASTM-E-648)</b>	≥ 0.45 (Class I)
<b>Smoke Density (NFPA-258-T or ASTM-E-662)</b>	≤ 450 Flaming and Non-Flaming
<b>Static Electricity (AATCC-134) 20% R.H., 70° F.</b>	≤ 3.5 KV
<b>Dimensional Stability - Aachener Test (DIN Std 54318)</b>	≤ 0.2%
<b>Texture Appearance Retention Rating (TARR)</b>	Severe Traffic End-Use Applications
<b>Recommended Maintenance</b>	MilliCare® Textile and Carpet Care Service Network
<b>Indoor Air Quality - CRI Green Label Plus™</b>	GLP0793, Carpet Category 5Y

Design © Milliken & Company. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice.



## Warranties:

Wear - 10 Year / 10% Fiber Loss

Staining/Soiling (StainSmart®)

Atmospheric Fading

Delamination of Backing

Antimicrobial Protection (AlphaSan®)

Edge Ravel

Flammability

Antistatic

Tuft Bind

Dimensional Stability

Heavy Wheeled Traffic

Floor Compatibility

Floor Release

Moisture Resistance

Cushion Resiliency