

TetraPointe

Milliken's Modular Series bases are standard with a moisture barrier attached pad and are constructed for the most demanding hospitality environments. You will enjoy exact pattern match, uncompromising beauty and relentless durability with Milliken's Modular Series. No other product comes with stronger performance warranties.

Construction	Tufted, Textured Loop Pile
Dye Method	Digital Millitron® Dye Injection
Face Fiber	100% WearOn® Continuous Filament Type 6,6 Nylon Twisted and Heat Set for Maximum Performance
Stain and Soil Protectant	StainSmart®
Mold/Mildew Odor Control	AlphaSan® Built-In Protection
Tufted Face Weight	20 oz./sq.yd. (678.1 g./sq.m.)
Tufting Gauge	1/10 (39.4/10 cm.)
Stitches	10.4/in. (40.9/10 cm.)
Tufting Density	104.0/sq.in. (1,611.5/100 sq.cm.)
Finished Pile Height	0.11 in. (2.8 mm.)
Density Factor	322,309
Average Density	6,545
Primary Backing	Synthetic Non-Woven
Secondary Backing	Attached Pad – ENHANCER™ Technology
Recycled Content	25% Pre-Consumer, 3% Post-Consumer
Nominal Total Thickness	0.34 in. (8.6 mm.)
Tile Size	36" x 36" (914.4 x 914.4 mm.)
Nominal Total Weight	102.4 oz./sq.yd. (3,472.1 g./sq.m.)
Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I)
Smoke Density (NFPA-258-T or ASTM-E-662)	≤ 450 Flaming and Non-Flaming
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV
Recommended Traffic (CRI TM101)	Severe Use
Recommended Maintenance	MilliCare® Textile and Carpet Care Service Network

Design Copyright – Milliken & Company. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice.



Applicable Milliken Warranties:

Wear -- 10 Year / 10% Fiber Loss
Staining/Soiling (StainSmart)
Atmospheric Fading
Delamination of Backing
Antimicrobial Protection (AlphaSan)
Edge Ravel

Flammability
Antistatic
Tuft Bind
Dimensional Stability
Heavy Wheeled Traffic
Floor Compatibility

Floor Release
Moisture Resistance
Cushion Resiliency

