

Tetra

Milliken's Modular Series bases are standard with a moisture barrier attached pad and are constructed for the most demanding hospitality environments. You will enjoy pattern match, uncompromising beauty and relentless durability with Milliken's Modular Series. No other product comes with stronger performance warranties.

| | |
|--|--|
| Construction | Tufted, Textured Loop Pile |
| Dye Method | Digital Millitron® Dye Injection |
| Face Fiber | Milliken WearOn® BCF Nylon Type 6,6 |
| Stain and Soil Protectant | StainSmart® |
| Mold/Mildew Odor Control | AlphaSan® Built-In Protection |
| Tufted Face Weight | 12 oz./sq.yd. (406.9 g./sq.m.) |
| Tufting Gauge | 1/10 (39.4/10 cm.) |
| Stitches | 14.4/in. (56.7/10 cm.) |
| Tufting Density | 144.0/sq.in. (2,234.0/100 sq.cm.) |
| Finished Pile Height | 0.09 in. (2.3 mm.) |
| Average Density | 4,800 |
| Primary Backing | Synthetic Non-Woven |
| Secondary Backing | PVC-Free Underscore™ ES Cushion |
| Recycled Content | 32% Pre-Consumer |
| Nominal Total Thickness | 0.27 in. (6.9 mm.) |
| Tile Size | 36" x 36" (914.4 x 914.4 mm.) |
| Nominal Total Weight | 86.7 oz./sq.yd. (2,939.8 g./sq.m.) |
| Flammability (Radiant Panel ASTM-E-648) | ≥ 0.45 (Class I) |
| Smoke Density (NFPA-258-T or ASTM-E-662) | ≤ 450 Flaming and Non-Flaming |
| Static Electricity (AATCC-134) 20% R.H., 70° F. | ≤ 3.5 KV |
| Dimensional Stability – Aachener Test (DIN Std 54318) | ≤ 0.2% |
| Texture Appearance Retention Rating (TARR) | Severe Traffic End-Use Applications |
| Recommended Maintenance | MilliCare® Textile and Carpet Care Service Network |
| Indoor Air Quality – CRI Green Label Plus™ | GLP0793, Carpet Category 5Y |

Design © Milliken & Company. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice.

**Warranties:**

Wear - 10 Year / 10% Fiber Loss
Staining/Soiling (StainSmart®)
Atmospheric Fading
Delamination of Backing
Antimicrobial Protection (AlphaSan®)
Edge Ravel

Flammability
Antistatic
Tuft Bind
Dimensional Stability
Heavy Wheeled Traffic
Floor Compatibility

Floor Release
Moisture Resistance
Cushion Resiliency