

Strato36

Milliken Performer Series - Milliken's Strato Base is made possible through Milliken's Convergence Technology™. Convergence Technology combines multi-level loop tufting with digital patterning to create a highly dimensional and textural product. Strato is also part of Milliken's Performer Series which comes standard with our StainSmart and ColorSeal Technology and extended warranty package. This unique new product allows state of the art Infinity tufting technology, digital pattern, color and performance to converge on the floor and is only available through Milliken Hospitality Carpet.

Specifications:

Fabric Construction	Convergence Technology™, Infinity tufted, precision multi-level loop
Dye Method	Millitron Digital Patterning
Carpet Fiber	100% Milliken WearOn® Continuous Filament Nylon, Type 6,6
Stain and Soil Protectant	StainSmart®
Bleach Resistance	ColorSeal®
Mold/Mildew Odor Control	AlphaSan®
Yarn Weight	36 Oz. Square Yard / 1220 gm/m ²
Tufting Gauge	5/64 Gauge
Stitches Per Inch / Stitches Per 10 cm	11.50 Stitches per Inch / 45.3 Stitches per 10 cm
Tufting Density	143 Tufts/Square Inch / 2217/10 cm ²
Density Factor	422,464
Finished Pile Thickness/high	Nominal .26" Multi-Level Loop / Nominal 6.6 mm Multi-Level Loop
Finished Pile Thickness/low	Nominal .09" Multi-Level Loop / Nominal 2.4 mm Multi-Level Loop
Total Thickness	Nominal .39" Multi-Level Loop / Nominal 9.9 mm Multi-Level Loop
Total Weight	68 Oz./Square Yard / 2305 gm/m ²
Primary Backing	Synthetic Woven
Secondary Backing	Synthetic Actionbac®
Width	13' 6" / 4.12m
Radiant Panel Test	Class I, Greater Than .45 Watts/cm ²
Smoke Chamber Test	Less Than 450 Flaming & Non-Flaming
Static Electricity (AATCC-134) 20% R.H. , 70 F)	< 3.5 KV
Recommended Maintenance	MilliCare Environmental Services®
Recommended Traffic	Heavy Commercial

Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

Optional Features Available:

Carpet Widths	9 foot, 12 foot - 2,500 sy minimum order requirement
Secondary Backing	PerformaBac2 - Moisture Barrier Pad
Secondary Backing	Attached pad - ENHANCER™ TECHNOLOGY
Finished Pile Thickness/Pad	Nominal .23" Multi-Level Loop / Nominal 5.9 mm Multi-Level Loop
Total Thickness/Pad	Nominal .44" Multi-Level Loop / Nominal 11.0 mm Multi-Level Loop
Total Weight/Pad	98 Oz./Square Yard / 3322 gm/m ²

Applicable Milliken Warranties include:

10 Year 10% Fiber Loss Wear Warranty	Edge ravel
Staining/Soiling (StainSmart®)	Antistatic
Bleach resistance (ColorSeal®)	Tuft bind
Antimicrobial protection (AlphaSan®)	Atmospheric fading
Floor compatibility	Additional warranties if purchased:
Flammability	Attached cushion resiliency
Delamination of backing	Attached cushion moisture barrier

