

TexturePlus

Max System Series – Milliken’s Max System Products are streamlined to meet performance requirements while providing the absolute best value and service in the industry. Low minimums and emergency response are not a problem when you combine the Max Color System with Milliken’s Service Series Bases. All Max System bases are available for 14 to 21 day shipment, the fastest and most flexible quick ship program in the industry.

Specifications:

Fabric Construction	Tufted, Patterned Textured Loop
Carpet Fiber	WearOn® Continuous Filament Nylon
Stain and Soil Protectant	MilliGuard®
Mold/Mildew Odor Control	AlphaSan®
Yarn Weight	29 Oz per Square Yard / 983 gm/m ²
Tufting Gauge	1/10 Gauge
Stitches Per Inch	12.5 Stitches Per Inch / 49.2 Stitches Per 10 cm
Tufting Density	125 Tufts per Square Inch / 1938 10 cm ²
Density Factor	348,320
Finished Pile Thickness	Imperial - Nominal .34 (high stitch) .19 (low stitch) Metric - 8.6 mm (high stitch) 4.8 mm (low)
Total Thickness, English	Imperial - Nominal .42 (high stitch) .27 (low stitch) Metric - 10.7 mm (high stitch) 6.9 mm (low stitch)
Total Weight	67 Oz./Square Yard / 2271 gm/m ²
Primary Backing	Synthetic Woven
Secondary Backing	Synthetic Actionbac®
Width	13' 6" / 4.12m
Radiant Panel Test	Class I, Greater Than .45 Watts/cm ²
Smoke Chamber Test	Less Than 450 Flaming & Non-Flaming
Static Electricity (AATCC-134) 20% R.H. , 70 F)	Less Than 3.5 KV
Recommended Maintenance	MilliCare Environmental Services®
Recommended Traffic	Commercial

Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

Optional Features Available:

Bleach Resistance	ColorSeal®
Secondary Backing	PerformaBac2 - Moisture Barrier Pad
Secondary Backing	Attached pad - ENHANCER™ TECHNOLOGY
Finished Pile Thickness/Pad	Imperial - Nominal .34" (high stitch), .19 (low stitch) Metric - 8.7 mm (high stitch) 4.8 mm (low stitch)
Total Thickness/Pad	Imperial - Nominal .55 (high stitch) .40 (low stitch) Metric - 14.0 mm (high stitch) 10.2 mm (low stitch)
Total Weight/Pad	101 Oz./Square Yard / 3424 gm/m ²

Applicable Milliken Warranties include:

10 Year 10% Fiber Loss Wear Warranty	Edge ravel
MilliGuard 5 Year Stain/Soil Warranty	Flammability
Atmospheric fading	Antistatic
Delamination of backing	Additional warranties if purchased:
Tuft bind	Bleach resistance (ColorSeal®)
Floor compatibility	Attached cushion moisture barrier
Antimicrobial protection (AlphaSan®)	Attached cushion resiliency

