

Max 42

MAX OR MOD COLORS

Milliken's Max System Products are streamlined to meet performance requirements while providing the absolute best value and service. Low minimums and emergency response are not a problem when you combine our standard color options (Max and Mod Colors) with Milliken's Service Series Bases. All Max System bases are available with 14 to 21 day shipment, the fastest and most flexible quick ship program in the industry.

Construction	Tufted, Patterned Cut Pile
Dye Method	Digital Millitron® Dye Injection
Colorways Available	Max or Mod Colors
Face Fiber	Milliken WearOn® BCF Nylon Type 6,6
Stain and Soil Protectant	MilliGuard®
Mold/Mildew Odor Control	AlphaSan® Built-In Protection
Tufted Face Weight	42 oz./sq.yd. (1,424.1 g./sq.m.)
Tufting Gauge	1/10 (39.4/10 cm.)
Stitches	11.85/in. (46.7/10 cm.)
Tufting Density	118.5/sq.in. (1,840.0/100 sq.cm.)
Finished Pile Height	0.27 in. sheared (6.9 mm.)
Average Density	5,600
Primary Backing	Synthetic Woven
Secondary Backing	Endura-Loc™
Recycled Content with Endura-Loc	1% Pre-Consumer
Recycled Content with optional attached pad	1% Pre-Consumer, 12% Post-Consumer, 3% Rapidly Renewable
Nominal Total Thickness	0.35 in. sheared (8.9 mm.)
Width	13'6" (4.11 m.)
Nominal Total Weight	73.0 oz./sq.yd. (2,475.2 g./sq.m.)
Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I)
Smoke Density (NFPA-258-T or ASTM-E-662)	≤ 450 Flaming and Non-Flaming
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV
Texture Appearance Retention Rating (TARR)	Severe Traffic End-Use Applications
Recommended Maintenance	MilliCare® Textile and Carpet Care Service Network
Indoor Air Quality – CRI Green Label Plus™	GLP2860, Carpet Category 1Y
Optional Features Available:	
Stain and Soil Protection	StainSmart®
Bleach Resistance	ColorSeal®
Carpet Widths	9' and 12' (200 sq. yd. minimum for 9' width)
Secondary Backing - Attached Cushion	Cushion-Loc™ featuring Enhancer™ Technology (500 sq. yd. min., 9' not available)
Secondary Backing - Attached Cushion w/Moisture Barrier	Moisture-Bloc™ featuring Enhancer™ Technology (500 sq. yd. min., 9' not available)
Nominal Total Thickness with Attached Cushion	0.51 in. sheared (13.0 mm.)
Nominal Total Weight with Attached Cushion	107.0 oz./sq.yd. (3,628.1 g./sq.m.)

Design © Milliken & Company. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice.

**Warranties:**

Wear - 10 Year / 10% Fiber Loss	Edge Ravel
MilliGuard® 5 Year Stain/Soil Warranty	Flammability
Atmospheric Fading	Antistatic
Delamination of Backing	Tuft Bind
Antimicrobial Protection (AlphaSan®)	Floor Compatibility

Additional warranties if purchased:

- Staining/Soiling (StainSmart®)
- Bleach Resistance (ColorSeal®)
- Moisture Barrier (Moisture-Bloc™ backing)
- Cushion Resiliency (Cushion-Loc™ backing)