

# MaxRooms 32

## MAX OR MOD COLORS

Milliken's Max System Products are streamlined to meet performance requirements while providing the absolute best value and service. Low minimums and emergency response are not a problem when you combine our standard color options (Max and Mod Colors) with Milliken's Service Series Bases. All Max System bases are available with 14 to 21 day shipment, the fastest and most flexible quick ship program in the industry.

<b>Construction</b>	Tufted, Patterned Cut Pile
<b>Dye Method</b>	Digital Millitron® Dye Injection
<b>Colorways Available</b>	Max or Mod Colors
<b>Face Fiber</b>	Milliken WearOn® BCF Nylon Type 6,6
<b>Stain and Soil Protectant</b>	MilliGuard®
<b>Mold/Mildew Odor Control</b>	AlphaSan® Built-In Protection
<b>Tufted Face Weight</b>	32 oz./sq.yd. (1,085.0 g./sq.m.)
<b>Tufting Gauge</b>	1/10 (39.4/10 cm.)
<b>Stitches</b>	10.75/in. (42.3/10 cm.)
<b>Tufting Density</b>	107.5/sq.in. (1,666.0/100 sq.cm.)
<b>Finished Pile Height</b>	0.22 in. sheared (5.6 mm.)
<b>Average Density</b>	5,236
<b>Primary Backing</b>	Synthetic Woven
<b>Secondary Backing</b>	Endura-Loc™
<b>Recycled Content with Endura-Loc</b>	1% Pre-Consumer
<b>Recycled Content with optional attached pad</b>	1% Pre-Consumer, 13% Post-Consumer, 3% Rapidly Renewable
<b>Nominal Total Thickness</b>	0.30 in. sheared (7.6 mm.)
<b>Width</b>	13'6" (4.11 m.)
<b>Nominal Total Weight</b>	64.0 oz./sq.yd. (2,170.1 g./sq.m.)
<b>Flammability (Radiant Panel ASTM-E-648)</b>	≥ 0.45 (Class I)
<b>Smoke Density (NFPA-258-T or ASTM-E-662)</b>	≤ 450 Flaming and Non-Flaming
<b>Static Electricity (AATCC-134) 20% R.H., 70° F.</b>	≤ 3.5 KV
<b>Texture Appearance Retention Rating (TARR)</b>	Heavy Traffic End-Use Applications
<b>Recommended Traffic</b>	Hotel Guestrooms
<b>Recommended Maintenance</b>	MilliCare® Textile and Carpet Care Service Network
<b>Indoor Air Quality - CRI Green Label Plus™</b>	GLP2860, Carpet Category 1Y
<b>Optional Features Available:</b>	
<b>Stain and Soil Protection</b>	StainSmart®
<b>Bleach Resistance</b>	ColorSeal®
<b>Carpet Widths</b>	9' and 12' (200 sq. yd. minimum for 9' width)
<b>Secondary Backing - Attached Cushion</b>	Cushion-Loc™ featuring Enhancer™ Technology (500 sq. yd. min., 9' not available)
<b>Secondary Backing - Attached Cushion w/Moisture Barrier</b>	Moisture-Bloc™ featuring Enhancer™ Technology (500 sq. yd. min., 9' not available)
<b>Nominal Total Thickness with Attached Cushion</b>	0.44 in. sheared (11.2 mm.)
<b>Nominal Total Weight with Attached Cushion</b>	98.0 oz./sq.yd. (3,322.9 g./sq.m.)

Design © Milliken & Company. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice.

**Warranties:**

Wear - 10 Year / 10% Fiber Loss	Edge Ravel
MilliGuard® 5 Year Stain/Soil Warranty	Flammability
Atmospheric Fading	Antistatic
Delamination of Backing	Tuft Bind
Antimicrobial Protection (AlphaSan®)	Floor Compatibility

**Additional warranties if purchased:**

Staining/Soiling (StainSmart®)
Bleach Resistance (ColorSeal®)
Moisture Barrier (Moisture-Bloc™ backing)
Cushion Resiliency (Cushion-Loc™ backing)