

Royal Texture 32

Milliken's Performer Series products are constructed for heavy commercial hospitality environments and come standard with two of Milliken's proprietary enhancement technologies: StainSmart for resistance, repellency and releasability of stains and soil; ColorSeal for bleach resistance. No other patterned carpet in the hospitality industry offers the performance attributes that cover all of your carpet concerns. Milliken backs the Performer Series with unmatched warranties for wear, stains, soil and bleach.

Construction	Tufted, Cut/Loop Tip Shear
Dye Method	Digital Millitron® Dye Injection
Face Fiber	Milliken WearOn® BCF Nylon Type 6,6
Stain and Soil Protectant	StainSmart®
Mold/Mildew Odor Control	AlphaSan® Built-In Protection
Bleach Resistance	ColorSeal®
Tufted Face Weight	34 oz./sq.yd. (1,152.9 g./sq.m.)
Tufting Gauge	5/64 (50.4/10 cm.)
Stitches	12.33/in. (48.5/10 cm.)
Tufting Density	157.8/sq.in. (2,444.4/100 sq.cm.)
Finished Pile Height	0.18 in. sheared (4.6 mm.)
Average Density	6,924
Primary Backing	Synthetic Woven
Secondary Backing	Endura-Loc™
Recycled Content with Endura-Loc	1% Pre-Consumer
Recycled Content with optional attached pad	1% Pre-Consumer, 13% Post-Consumer, 3% Rapidly Renewable
Nominal Total Thickness	0.28 in. sheared (7.1 mm.)
Width	12' (3.65 m.)
Nominal Total Weight	65.0 oz./sq.yd. (2,204.0 g./sq.m.)
Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I)
Smoke Density (NFPA-258-T or ASTM-E-662)	≤ 450 Flaming and Non-Flaming
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV
Texture Appearance Retention Rating (TARR)	Heavy Traffic End-Use Applications
Recommended Maintenance	MilliCare® Textile and Carpet Care Service Network
Indoor Air Quality - CRI Green Label Plus™	GLP2860, Carpet Category 1Y

Optional Features Available:

Secondary Backing - Attached Cushion	Cushion-Loc™ featuring Enhancer™ Technology (500 sq. yd. min.)
Secondary Backing - Attached Cushion w/Moisture Barrier	Moisture-Bloc™ featuring Enhancer™ Technology (500 sq. yd. min.)
Nominal Total Thickness with Attached Cushion	0.35 in. sheared (8.9 mm.)
Nominal Total Weight with Attached Cushion	101.0 oz./sq.yd. (3,424.6 g./sq.m.)

Design © Milliken & Company. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice.



Warranties:

Wear - 10 Year / 10% Fiber Loss	Edge Ravel
Staining/Soiling (StainSmart®)	Flammability
Antimicrobial Protection (AlphaSan®)	Antistatic
Bleach Resistance (ColorSeal®)	Tuft Bind
Atmospheric Fading	Floor Compatibility
Delamination of Backing	

Additional warranties if purchased:

Moisture Barrier (Moisture-Bloc™ backing)
Cushion Resiliency (Cushion-Loc™ backing)